



SMART LIGHT 1000™

INSTALLATION AND OPERATIONS INSTRUCTIONS

THANK YOU FOR CHOOSING THE SMART LIGHT 1000™!

We are very pleased that you have chosen our product to enhance your camping experience! At Starlights, Inc., we are passionate about improving your safety, security, and convenience. We feel that the **Smart Light 1000™** represents a giant step forward in improving an already wonderful experience – Rving!

Developed and designed in the United States, by RVers, for RVers, the **Smart Light 1000™** has the versatility to adapt to differing park conditions, or to dry camping conditions. Your new **Smart Light 1000™** also monitors your battery levels, and will notify you of any serious reduction in power. We are confident that you will be completely satisfied with your new **Smart Light 1000™** for years to come. Happy camping!

Jason P. Weaver
President, CEO
Starlights, Inc.

CONTENTS of Box

The **Smart Light 1000™** packaging should include the following parts to make the installation simple and convenient.

1. One lighting fixture
 2. Four mounting screws
 3. 2ea. Butt connectors
 4. Instruction Manual
-

BULB REQUIREMENT for the **Smart Light 1000™**--- **Incandescent “1003” Bulb** or the **NEW "Revolution LED line of Bulbs"**. This New line of LED Bulbs can be reviewed at www.starlightsinc.com

OPTIONAL ACCESSORIES

- **Revolution LED Bulbs.**
 - **Smart Light 2000™ Motion Light**
 - **Smart Light 2000 Scare Light™**
 - **Revolution 2000 FB™ Fused Relay Box**
 - **Amberizer™ Antibug Bulbs**
 - **Amber Lens**
-

INSTALLATION & SAFETY INSTRUCTIONS

For the **Smart Light 1000™** RV Motion Light

IMPORTANT SAFETY INFORMATION

- ✓ Disconnect battery before installing or replacing the motion sensor lighting fixture.

- ✓ **This product must be installed in accordance with any state and national codes by a person familiar with the construction and operation of the product and hazards involved.**
- ✓ This motion sensor light is designed to be used only with 12 DC Power [Automotive type], any modifications of the unit may result in a hazard and will VOID the warranty.
- ✓ Please do not attempt to open the *Motion Sensor back housing* as there are no serviceable parts inside and doing so **WILL VOID** the warranty.
- ✓ Please read all of the **Smart Light 1000™** installation instructions before installing the fixture.

IMPORTANT NOTES

- Attaching other accessories or devices without the uses of the **Revolution 2000 FB™ Fused Relay Box** can cause a hazard, may damage the unit, and **WILL VOID the WARRANTY.**

INSTALLING the Smart Light 1000™

IMPORTANT-DISCONNECT THE BATTERY

STEP 1: Remove the old lighting fixture from the RV and clean area of all old sealer, dirt, etc.

STEP 2: Attach the BLACK or WHITE wire marked positive (+) on the SL-1000 fixture to the positive wire (+) coming from the RV.

STEP 3: Attach the WHITE wire marked negative (-) on the SL-1000 fixture to the negative wire (-) coming from the RV.

NOTE: If there are other accessories or devices that together total less than 4 amps that you would like to trigger using the **Smart Light 1000™** you can trigger them by using the **Revolution 2000 FB™ Fused Relay Box**. The **Revolution 2000 FB™ Fused Relay Box** is triggered using the **YELLOW** wire located on the back of the fixture and will supply voltage to the accessories while protecting the circuitry of the **Smart Light 1000™**. The **YELLOW** wire is shrink wrapped to the Power wire. To access the **YELLOW** wire, remove the shrink wrap.

NOTE: Perform functionality test at this step

The **Smart Light 1000™** is **reverse polarity protected**. If it is wired backwards, the unit will not be damaged. However, if wired incorrectly, the motion sensing functionality will not work, even though the light can be turned on and off at the switch as with any other porch light. Thus, it is imperative that you perform this self test in order to assure proper functionality. To do this test you will have to reconnect the battery.

First, adjust your interior light switch to the on position. Then, turn the light switch off, then on again. If at this point you find that the light turns on, but the **BLUE LED does not**

blink on and off then switch the positive and negative wires connecting the Smart Light to your vehicle. Next, perform the self test once again as described above. If your light again fails to operate in the auto mode as indicated, please stop the installation process and contact us at 1-800-883-5444. If the functionality test is successful, again **DISCONNECT THE BATTERY** and proceed with the installation.

STEP 4: Remove the FIVE (5) screws that attach the lens on the **Smart Light 1000™** fixture **taking care not to lose the small O-ring on the backside of the lens where the oval is** and save them to reattach the lens in STEP (6). Place a bead of silicone sealant on the backside of the fixture in the shear groove, *being careful not to plug the water drain groove at the bottom of the Smart Light 1000™ fixture*. Use the FOUR (4) screws provided, or the (4) screws from your old fixture, to attach the **Smart Light 1000™** fixture to the exterior of the RV. In most cases, the previous holes used to mount the old fixture can be reused to mount the **Smart Light 1000™**. However, if you must drill new screw holes into your substrate, make sure to properly fill in the old holes before mounting your light.

NOTE:

Some models may have differing hole depths and/or widths. Thus, the screws provided may not be sufficient. If you find this to be the case on your model, simply substitute the enclosed screws for those that will fasten the unit properly.

STEP 5: Adjustment of the Variable Resistor (*Potentiometers*) for sensitivity is clockwise to increase sensitivity, and counterclockwise to decrease sensitivity. When adjusting this resistor, take care not to touch the mother board, which could damage the unit and **WILL VOID the WARRANTY**. Please note that the **Smart Light 1000™** fixture comes from the factory set at the *most sensitive setting and may need adjustment to a lower sensitive setting to match the camping environment*.

IMPORTANT – DISCONNECT THE BATTERY BEFORE ADJUSTING

The *Potentiometers* are located on the circuit board mounted in the electronics compartment of the **Smart Light 1000™** fixture. Once the lens has been removed, access for adjustment is through the opening, with the Potentiometers located *above* the light sensor and *below* the multicolored LED. Note that the bottom potentiometer is for the right sensor, and the top potentiometer is for the left sensor. Take great care when adjusting not to touch the circuit board, which would void the warranty.

Please keep in mind outside temperatures when adjusting sensitivity.

PIR (PASSIVE INFRARED SENSOR) NOTE:

A note about this state of the art technology: These PIR sensors detect thermal mass. Additionally, the internal micro processor embedded in your **Smart Light 1000™** “communicates” with the PIR sensors in code. This code allows your **Smart Light 1000™** fixture to differentiate between a large thermal mass, and a small one (such as a cat, rabbit, small dog, etc.). When a small thermal mass is detected, the code tells the light not to turn on. When a larger mass is detected (i.e. humans, a bear, large dogs, etc.) the code enables the unit to turn on the light. However, thermal readings are dictated by outside temperatures. It is more difficult to trigger the fixture when the background temperature is close to the outside body temperature of the object moving across it, making it necessary to come closer to the fixture to turn it on. Likewise, if it’s very cold outside, the cold background makes it much easier to pick up any thermal mass, and thus the PIR sensors may detect an object further away than normal.

STEP 6: Replace the lens using the FIVE (5) screws removed in STEP (4).

VERY IMPORTANT: Please ensure that the **CLEAR** O-RING which seals the electronics compartment is located properly on the back side of the Lens cover where the oval is. If this small O-RING is missing when the cover is reinstalled, water may intrude into the electronics compartment and disable the fixture. *The O-RING is embedded in the lens directly over the electronics compartment oval access hole. To ensure proper placement of the O-Ring, rub your index finger around the outside of the oval portion of the lens which covers the electronics compartment. If you are unable to locate the O-RING, please contact us before installing the fixture.*

You may now reconnect the Battery.

IMPORTANT NOTE:

The **Smart Light 1000™** fixture was designed to operate in two (2) modes:

Mode 1 – Manual Mode

The Manual mode is triggered when switched “ON” by the **off-on switch** located inside the RV. In the manual mode, the daylight sensor will be inoperable and the **Smart Light 1000™** will work as a standard lighting product with the exception of **Star Monitor™**

Starlight’s exclusive **Star Monitor™** will monitor the RV’s Battery Voltage Level. When the voltage drops to 11.5 volts for 45 consecutive seconds, a **RED** led will blink behind the lens as a warning of a low battery condition. **Star Monitor™** will not turn the **Smart Light 1000™** fixture off in this mode, but it will issue a warning. As a side note, several customers have called over the years claiming the **Star Monitor™** is inaccurate. Our trouble shooting efforts found that every customer had some sort of electrical malfunction. The **Star Monitor™** utilizes a digital code and is 99.999% accurate. Thus, if

you see the RED LED flash, please take care and check every facet of your electrical system.

Mode 2 - Auto Mode

The Auto mode is triggered by an “ON-OFF-ON” switching of the **off-on light switch** located inside the RV. However, if the fixture is already powered up in Manual Mode, then switching the fixture “OFF then ON” will trigger the Auto Mode function. In the Auto Mode, the daylight sensor, *Star Monitor*TM, and motion sensors are operable. Once the **Smart Light 1000**TM detects motion it will activate the bulb and stay on for one (1) minute. If the fixture again detects motion before the (1) minute is up, then the timer will reset, and the count-down will recommence. If no other motion is detected, then the light will deactivate, and the area around your coach will continue to be monitored. Finally, don’t be alarmed if the **Smart Light 1000**TM does not detect your motion at the exact same point each time. A variety of factors dictate when and at which point the motion detection units will activate the light bulb. If you have questions about this nuance, please contact our engineering help desk for a more thorough explanation.

Starlight’s’ exclusive *Star Monitor*TM continues to monitor the RV’s Battery Voltage Level. If the voltage drops to the predetermined level, a **RED** LED will blink behind the lens as a warning of a low battery condition. *Star Monitor*TM will, in the auto mode, turn the **Smart Light 1000**TM fixture off. When the battery rises past the predetermined level, the **Smart Light 1000**TM fixture will reset itself automatically and continue operation.

Side note: Customers have asked why we deactivate the **Smart Light 1000**TM at 11.5 volts. The reason is that at this voltage level, most of your major appliances will cease to operate (such as your refrigerator). Also, at 11.5 volts, your batteries are working at less than 35% capacity.

The **Smart Light 1000**TM has three (3) operating phases as listed below:

1. When activated in the “**DAY-TIME Auto Mode**” function, the Multi-Colored LED will blink “**BLUE**”. This indicates that the fixture is activated, it is daytime, your battery is charged, and that the unit will not illuminate if it senses motion.
2. When activated in the “**NIGHT-TIME Auto Mode**” function, the Multi-Colored LED will blink “**GREEN**”. This indicates that the unit is activated, it is dark outside, your battery is charged, and that the light will illuminate if the proper motion is detected.
3. When the **Smart Light 1000**TM fixture is in either mode and the *Star Monitor*TM function has been activated by a low battery condition, the Multi-Colored LED will blink “**RED**”. Regardless of the time of day, the light will not illuminate with any motion until the low battery condition is remedied.

Smart Light 1000™ Trouble Shooting Guide

SYMPTOM	CAUSE	POSSIBLE SOLUTION
Light won't come on.	• Power not on.	• Turn on indoor switch or check fuse.
	• Grounded incorrectly.	• Check ground wire.
	• Light bulb blown.	• Check bulb and replace if necessary.
While in Porch Light Mode the LED flashes "RED" but the Light Bulb does work.	• Low Battery Condition - <i>(Line Voltage to fixture dropped to 11.5 Volts or below for a period of 45 seconds).</i>	• Charge or replace the Coach the Battery. • Check breaker on Coach charging system and reset if necessary.
	• Too much load on wire supplying power to the fixture.	• Up-size wire gauge from distribution panel to Fixture.
		• Up-size wire gauge to distribution panel from battery.
Smart Light 1000™ only works as a Porch light	• SL1000™ wired wrong	• Switch power leads to fixture.
Light stays on in AUTO MODE. SL1000™ will not energize the bulb in auto mode when there is motion within the detection area	• Fixture operating in PORCH LIGHT MODE.	• Re-program with indoor switch.
	• Wired incorrectly.	• Check that wiring is connected properly.
	• Frequent changes in heat are being detected.	• Check sensing area for possible heat sources i.e. water heater exhaust, moving vehicles, or other heat source. Adjust the sensitivity to a less sensitive setting.
	• The SL1000™ is blinking "BLUE" not "GREEN"	• Wait until night time, as the SL1000™ will not change modes until the outside light has dropped to a certain Luminous level. • Make sure that a street light, parking lot lighting or other bright light is not directly shinning on the fixture. • Wait until the fixture has time to determine which mode to operate in. It always defaults to daytime mode once triggered and takes 30 seconds to change modes.
Light keeps cycling "ON" & "OFF"	• Changes in heat are being detected from a fixed heat source	• Check the field of view for hot gas vents, camp fires, or other heat sources. If possible, reposition your coach.
	• Light and Heat are being reflected back onto the sensor	• Mask reflective surfaces to eliminate the reflection, or reposition the coach if possible.
	• Sudden temperature changes due to storms or high winds or rain	• Turn sensor off until storm passes.
While in "Auto Mode" the LED flashes "RED" but the Light Bulb does "NOT" Work.	• Low Battery Condition - <i>(Line Voltage to fixture dropped to 11.5 Volts or below for a period of 45 seconds).</i>	• Start the generator if applicable. Otherwise, charge or replace the Coach the Battery. • Check breaker on Coach charging system and reset if necessary.
	• Too much load on wire supplying power to the fixture.	• Up-size wire gauge to distribution panel from battery.

LIMITED WARRANTY

This product is warranted free from defects in material and workmanship for a period of one year. If a defect in material or workmanship occurs, call (805) 685-8500 or (800) 883-5444 for instructions on how to have the defective product repaired or replaced.

LIMITATIONS

- This warranty is extended only to the original purchaser of the product.
- This warranty only covers the assembled motion lighting fixture.
- Unauthorized service to, or modification of this product will void the warranty in its entirety.
- A **purchase receipt or other approved proof of purchase** is required before warranty service is rendered.
- This warranty is expressly in lieu of all other warranties, expressed or implied, including any warranty, representation or condition of merchantability or that the products are fit for any particular purpose or use, and specifically in lieu of all special, indirect, incidental, or consequential damages, including but not limited to, any loss arising out of any breach of this warranty, as allowed by your state of domicile.
- This warranty gives you specific rights, and you may also have other rights that vary from state to state.

NOT COVERED

- Failure of the product as a result of an accident, abuse, negligence, alteration, or faulty installation, or any other failure not relating to faulty material or workmanship.
- Reimbursement for inconvenience, installation, setup, time, loss of use, postage or unauthorized service.

CAUTION: This unit should yield many years of quality service. However, to avoid damaging the **Smart Light 1000™** fixtures Fresnel lenses and sensors, do not spray the **Smart Light 1000™** fixture directly with a high-pressure hose, or pressure washer.

If it is necessary to return any Starlight product, please get a **RETURN CONFIRMATION NUMBER** by calling (805) 685-8500 or (800) 883-5444. *Then send the unit back in its original box with all original parts, as well as a copy of your receipt and a brief explanation of what kind of failure you experienced, to the address below.*

GENERAL CORRESPONDENCE

Starlights, Inc.
PO Box 80246
Goleta, CA 93118
Phone (805) 685-8500
Phone (800) 883-5444
Fax (805) 685-3754

THANK YOU FOR
YOUR TRUST IN US!



RETURNS:

Starlights, Inc.
283 Pamela Way,
Unit 104
Buellton, CA 93427

For technical issues:

Gregg Wilson

gregg.wilson@starlightsinc.com