Product Information Sheet

Product: In-line Check Valve

Models: 340-000/001, 1/2" [13mm] Barb OEM/Aftermarket

Caution: Do not use for Water Heaters

Technical Specifications

Cracking Pressure: 1 psi [.1 bar]

Max. Pressure: 100 psi [6.9 bar]

Overall Dimensions: 4-1/4" x 1-5/8" [108 mm x 42 mm]

Temperature Limits: $34^{\circ}F - 120^{\circ}F [1^{\circ}C - 49^{\circ}C]$

Fitting Configuration: 1/2" x 1" [13 x 25mm] Straight Barb
Materials: Nylon, EPDM. All materials are NSF Listed.

Installation

- 1. Arrow on body must be pointed in the same direction as the flow.
- 2. Do not use with fluids that contain particulate matter.
- 3. Be sure connections are secured with properly sized hose clamps.
- 4. Make sure all connections are in accordance with application.
- 5. Check for leaks after installation.





SHURflo reserves the right to update specifications, prices, or make substitution

SHURflo, LLC Headquarters 5900 Katella Ave. Cypress, CA 90630 Phone (562) 795-5200 Toll Free(800) 854-3218 FAX (562) 795-7554

SHURflo, LLC East 52748 Park Six Court Elkhart, IN 46514-5427 Phone (562) 795-5200 Toll Free (800) 854-3218 FAX (574) 264-2169 © 1999 All rights reserved SHURflo Europe, Middle East, Africa Pentair Water Belgium bvba, Industriepark Wolfstee, Toekomstlaan 30 B-2200 Herentals, Belgium Phone +32-14-283500 Fax +32-14-283505

911-542-D 03/09 ECO 16260

911-542-D 03/09 ECO 16260 Page 1