

Convenience Center Operation Instructions (CYCLONE / ROAD WARRIOR)

SELECTOR VALVE OPERATION:

Normal: (Dry camping): Pumping from on-board tank with the on-board pump.

City: Diverting water pressure from hose connected to inlet backflow preventer to the fixtures in the RV.

Tank Fill: Diverting water pressure from hose to the on-board fresh water holding.

Sanitize/Winterize: Drawing water, sanitizer, or RV grade winterizer from bucket through a hose connected to the inlet backflow preventer using the on-board pump and diverting this flow to the fixtures.

A. Filling Water Tank Using Selector Valve:

Caution – Never leave your coach unattended while filling the fresh water tank! Although proper venting is allowed for overflow, the water pressure can expand the tank and cause severe damage to your unit.

1. Connect hose to Selector Valve Hub.
2. Turn Selector Valve to tank.

B. Flushing black water holding tank:

1. Connect sewer hose to termination and to the dump station.
2. Open black water tank valve.
3. Connect a city water hose to the tank wash hub. **Important! Do not** turn on water yet!
4. Check to see if all of the above steps have been done before turning the water on to rinse the tank!
5. Leave the water on until you are satisfied that the tank has been thoroughly rinsed.
6. Turn off the water, close tank valve, and disconnect the sewer hose.

C. Water heater by-pass operation:

1. Water Heater By-Pass is located on back of the Water Heater.

D. To winterize the coach:

1. Turn the Selector Valve to Sanitize/Winterize position.
2. Drain the water heater by removing the anode rod and fully opening the relief valve.
3. Connect a short hose to the Selector Valve Hose Hub. Place the opposite end of the hose into a container of **non-toxic** anti-freeze.
4. Turn on the water pump.
5. Anti-freeze will be drawn from the container through the fresh water system by opening all faucets, (hot and cold) and also by stepping on the toilet water pedal until anti-freeze can be seen running through each faucet and also the toilet.
6. Once you have determined that all water lines have been winterized with anti-freeze, turn off the water pump and remove the hose.

